

Pipe Flashing

Square and round base pipe flashing
For roof pipe flashing

- Pipe opening can be easily customized on job sight utilizing clearly marked pipe diameters on each flashing.
- EPDM and Silicone are both flexible materials, resistant to ultraviolet rays, cracking or weathering.
- Available in EPDM black or gray and silicone red.

- The aluminum base is corrosion resistant and conforms easily to any panel configuration or roof pitch.
- Retrofit flashing is available for piping with welded caps or cross bars.
- Square base also available in white, terra cotta, bright red, light green, dark green, light blue and dark blue.

Application

Square Base

Size	Pipe size	Base size
1	1/4 – 2"	4-1/2"
2	1-1/4 – 3"	6"
3	1/4 – 4"	8"
4	3 – 6"	10"
5	4 – 7"	11"
6	5 – 9"	12"
7	6 – 11"	14"
8	7 – 13"	17"
9	10 – 18"	25"
10	13 – 26"	34"



Round Base

Size	Pipe size	Base Size
1	1/4 – 2"	4-3/4"
2	1-3/4 – 3-1/4"	6-1/4"
3	1/4 – 5"	7-3/4"
4	3 – 6-1/4"	9-1/4"
5	4-1/4 – 7-1/2"	10-3/4"
6	5 – 9"	12-1/4"
7	6 – 11"	14-1/4"
8	7 – 13"	16-1/2"
9	10 – 19"	25-1/2"



Material Specifications

Test Type	EPDM	Silicone (Hi-Temp)
Advance ozone resistance test @ 500 pphm	70 Hrs.	70 Hrs.
High temperature:		
Intermittent	+275° F	+500° F
Continuous	+212° F	+437° F
Low temperature:		
Resistance tested to	-65° F	-100° F
Tensile strength	1450 psi	700 psi



Options

None



Distributed by: 91-104 Kalaeloa Blvd, Kapolei HI 96707
 Ph: 808.682.3000 • Fax: 808.682.3636