

**EVERGRIP® 300 Series
Stainless Fasteners**

EVERGRIP stainless bi-metal
For metal to wood



EVERGRIP® stainless wood fastener is designed to self-drill metal panels:

- Head and the majority of shank is 300 Series Stainless Steel, with a welded, hardened carbon steel point for self-drilling performance.
- Provides the corrosion protection of stainless with the drill performance of a carbon steel fastener.
- Designed specifically for superior corrosion resistance in all wood treatments.
- Available with HWH or TORX drive pan head.

Application

**EVERGRIP®
9–15 HWH Sharp Point
Metal to wood**


Drilling capacity: 24 ga (0.024)
Self-drills through the metal panel and taps into wood substrate. Min penetration in wood substrates should be no less than 1"



1/4" Hex Washer Head
Thread Major Dia: 0.181 – 0.175
Thread Minor Dia: 0.133 – 0.127
Strength (lbs ult.):
Tensile: 1657
Torsional: 50 in-lbs min.
Shear: 1550

**EVERGRIP®
9–15 T-25 (TORX®) Pan Head
Metal to wood**

Drilling capacity: 24 ga (0.024)
Self-drills through the metal panel and taps into wood substrate. Min penetration in wood substrates should be no less than 1"



T-25 (TORX) Pan Head
Head Dia: 0.393–0.374"
Thread Major Dia: 0.181 – 0.175
Thread Minor Dia: 0.133 – 0.127
Strength (lbs ult.):
Tensile: 1657
Torsional: 50 in-lbs min.
Shear: 1550
Utilizing the special SFS T-25 Torx drive bit manufactured by SFS intec is recommended for superior stability during the installation process.

Notes

Dimensions are nominal inches unless noted. Pull out strength values may vary from tabulated loads depending upon specific wood density variations. Pull over strength values are based on AZ55 Galvalume steel material. Ultimate values listed are the result of laboratory testing. The specific job conditions should be considered and appropriate safety factors applied.

Fasteners installed in less than 1" of solid wood may have an increased potential for sealing or connection failure over time. This may be due to the fasteners being stripped out during installation and/or due to the lack of adequate wood fiber material to hold the fastener in place during thermal movement cycles or other forces which may be exerted upon the connection.

Performance Pounds Ultimate

Description	Pull-out (lbs ult.) Wood: Spruce, Pine, Fir	Pull-over
EVERGRIP® Stainless Bond Seal	1-1/2" Penetration	29 ga: 378
	1" Penetration	26 ga: 519
		24 ga: 704

Continued on following page

EVERGRIP® 300 Series
Stainless Fasteners

EVERGRIP stainless bi-metal
For metal to wood

Selection

		Example Code					
		BM-	S3-	#9x	1-1/2-	HW1/4-	SB1/2
Description	Available Lengths (L)	Type	Material	Diameter	Length	Head Style	Washer
#9-15 EVERGRIP® HWH with Bond Seal 250/bag	1", 1-1/2", 2", 2-1/2"	BM-	S3-	#9x	L-	HW1/4-	SB1/2
#9-15 EVERGRIP® HWH with Bond Seal 100/box	1", 1-1/2", 2", 2-1/2"	BM-	S3-	#9x	L-	HW1/4-	SB1/2
#9-15 EVERGRIP® T-25 Pan Head with Bond Seal 250/bag	1", 1-1/2", 2", 2-1/2", 3"	BM-	S3-	#9x	L-	PN-T25-	SB1/2
Installation Tool: #514261 SFS Special T-25 TORX Drive Bit – T25-50-HEX1/4"							

Installation

Tools: 0 – 2500 rpm screw gun equipped with depth sensing nose piece.

The EVERGRIP® 9-15 T-25 (TORX) Pan Head requires a T-25 Torx drive bit.

Utilizing the special SFS T-25 Torx drive bit manufactured by SFS intec is recommended for superior stability during the installation process.

Use of impact guns or hammer drills is not recommended.

Options

Painted

